


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:221.5V I:0.1136A P:23.92W PF:0.9505 Lamp Flux:2961.5x1 lm		
NAME: 线条灯	TYPE:LED	WEIGHT:
SPEC.:LI-JE1200LM/W-CCT-SL-下发光-小蜂窝	DIM.: 60*75*1200	SERIAL No.:
MFR.: JT	SUR.:0.6*0.75*0.12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 123.81 lm/W			
MODEL	LSM 32-50CCT-silver	I _{max} (cd)	1797	S/MH(C0/180)	0.97
NOMINAL POWER(W)	24	LOR(%)	100.0	S/MH(C90/270)	1.08
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	2961.5	η UP,DN(C0-180)	0.0,50.0
NOMINAL FLUX(lm)	2961.5	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.0
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	1.15

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2023-04-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.560m [K=0.9974]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C90	C180	C270					γ	Φ zone	Φ total	%lum,lamp
10	1699	1738	1699	1738					0- 10	167.6	167.6	5.66,5.66
20	1429	1557	1429	1557					10- 20	455.0	622.6	21,21
30	1092	1253	1092	1253					20- 30	613.7	1236	41.7,41.7
40	779.7	906.6	779.7	906.6					30- 40	629.8	1866	63,63
50	403.2	490.5	403.2	490.5					40- 50	485.9	2352	79.4,79.4
60	217.2	258.4	217.2	258.4					50- 60	302.9	2655	89.6,89.6
70	124.8	139.9	124.8	139.9					60- 70	177.0	2832	95.6,95.6
80	55.36	67.26	55.36	67.26					70- 80	100.3	2932	99,99
90	0.0709	0.3368	0.0709	0.3368					80- 90	29.30	2961	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2023-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:65.0%
 Test Distance:7.560m [K=0.9974]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.560m [K=0.9974]
Remarks:

```

WEC AND CCEC

Test:U:221.5V I:0.1136A P:23.92W PF:0.9505 Lamp Flux:2961.5x1 lm					
NAME: 线条灯			TYPE:LED		WEIGHT:
SPEC.:LI-JE1200LM/W-CCT-SL-下发光-小蜂窝			DIM.: 60*75*1200		SERIAL No.:
MFR.: JT			SUR.:0.6*0.75*0.12		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.251	.143	.045	.244	.139	.044	.231	.133	.042	.219	.126	.041	.208	.121	.039		
2.0	.239	.131	.040	.233	.129	.040	.222	.124	.038	.212	.119	.037	.202	.114	.036		
3.0	.225	.120	.036	.220	.118	.035	.210	.114	.035	.201	.110	.034	.192	.107	.033		
4.0	.211	.110	.032	.206	.108	.032	.198	.105	.031	.190	.102	.031	.182	.099	.030		
5.0	.198	.101	.029	.193	.099	.029	.186	.097	.028	.179	.094	.028	.172	.092	.028		
6.0	.185	.093	.027	.182	.092	.026	.175	.090	.026	.169	.088	.026	.163	.086	.025		
7.0	.175	.086	.024	.171	.085	.024	.165	.084	.024	.160	.082	.024	.154	.080	.024		
8.0	.165	.080	.023	.162	.080	.023	.156	.078	.022	.151	.077	.022	.147	.075	.022		
9.0	.156	.075	.021	.153	.075	.021	.148	.073	.021	.144	.072	.021	.139	.071	.020		
10.0	.147	.071	.020	.145	.070	.020	.141	.069	.019	.137	.068	.019	.133	.067	.019		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.176	.157	.139	.151	.134	.120	.103	.092	.083	.059	.054	.048	.019	.017	.016	
2.0	.165	.132	.104	.142	.114	.090	.097	.079	.063	.056	.046	.037	.018	.015	.012	
3.0	.156	.114	.081	.134	.098	.070	.092	.068	.049	.053	.040	.029	.017	.013	.009	
4.0	.147	.100	.064	.126	.087	.056	.087	.060	.039	.050	.035	.023	.016	.011	.008	
5.0	.140	.089	.052	.120	.077	.045	.083	.054	.032	.048	.032	.019	.015	.010	.006	
6.0	.133	.081	.043	.114	.070	.038	.079	.049	.027	.046	.029	.016	.015	.009	.005	
7.0	.126	.073	.037	.109	.064	.032	.075	.045	.023	.044	.026	.013	.014	.009	.004	
8.0	.120	.068	.031	.104	.059	.027	.072	.041	.019	.042	.024	.012	.013	.008	.004	
9.0	.115	.063	.027	.099	.054	.024	.068	.038	.017	.040	.023	.010	.013	.007	.003	
10.0	.110	.058	.024	.094	.051	.021	.066	.036	.015	.038	.021	.009	.012	.007	.003	

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2023-04-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.560m [K=0.9974]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:221.5V I:0.1136A P:23.92W PF:0.9505 Lamp Flux:2961.5x1 lm										
NAME: 线条灯					TYPE:LED			WEIGHT:		
SPEC.:LI-JE1200LM/W-CCT-SL-下发光-小蜂窝					DIM.: 60*75*1200			SERIAL No.:		
MFR.: JT					SUR.:0.6*0.75*0.12			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.9	21.1	20.1	21.3	21.5	20.5	21.8	20.8	22.0	22.2
3H	20.6	21.8	20.9	22.0	22.2	21.2	22.4	21.5	22.6	22.9
4H	20.9	22.1	21.2	22.3	22.5	21.6	22.7	21.9	22.9	23.2
6H	21.2	22.3	21.5	22.5	22.8	21.9	22.9	22.2	23.2	23.5
8H	21.3	22.3	21.6	22.6	22.9	22.0	23.0	22.3	23.3	23.6
12H	21.4	22.3	21.7	22.6	22.9	22.1	23.1	22.4	23.3	23.6
4H 2H	20.2	21.3	20.5	21.5	21.8	20.7	21.8	21.0	22.1	22.3
3H	21.1	22.1	21.4	22.4	22.7	21.6	22.6	22.0	22.9	23.2
4H	21.6	22.5	21.9	22.8	23.1	22.1	23.0	22.5	23.3	23.6
6H	22.0	22.8	22.4	23.1	23.5	22.6	23.4	23.0	23.7	24.1
8H	22.2	22.9	22.6	23.3	23.6	22.8	23.5	23.2	23.9	24.2
12H	22.2	22.9	22.7	23.3	23.7	22.9	23.6	23.3	23.9	24.3
8H 4H	21.8	22.5	22.2	22.9	23.2	22.3	23.0	22.7	23.3	23.7
6H	22.4	23.0	22.8	23.4	23.8	22.9	23.5	23.3	23.9	24.3
8H	22.6	23.1	23.0	23.5	24.0	23.1	23.7	23.6	24.1	24.5
12H	22.7	23.2	23.2	23.6	24.1	23.3	23.8	23.8	24.2	24.7
12H 4H	21.8	22.4	22.2	22.8	23.2	22.2	22.9	22.7	23.3	23.7
6H	22.4	22.9	22.9	23.4	23.8	22.9	23.4	23.4	23.9	24.3
8H	22.7	23.1	23.1	23.6	24.0	23.2	23.7	23.7	24.1	24.6
Variations with the observer position at spacings:										
S = 1.0H	+ 0.5 / - 0.6					+ 0.5 / - 0.5				
1.5H	+ 0.4 / - 0.5					+ 0.4 / - 0.3				
2.0H	+ 0.9 / - 0.8					+ 1.1 / - 0.8				

CIE Pub.117 Corrected 2961 lm Total Lamp Luminous Flux. (8log(F/F0) = 3.8)

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2023-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:65.0%
 Test Distance:7.560m [K=0.9974]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:221.5V I:0.1136A P:23.92W PF:0.9505 Lamp Flux:2961.5x1 lm		
NAME: 线条灯	TYPE:LED	WEIGHT:
SPEC.:LI-JE1200LM/W-CCT-SL-下发光-小蜂窝	DIM.: 60*75*1200	SERIAL No.:
MFR.: JT	SUR.:0.6*0.75*0.12	Shielding Angle:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	68	59	53	68	59	53	67	58	53	47
0.80	78	69	63	77	68	62	76	67	62	56
1.00	85	76	71	84	76	70	82	77	70	64
1.25	91	83	78	90	82	77	88	81	76	70
1.50	96	88	82	94	87	82	91	85	81	75
2.00	101	94	89	99	93	88	96	91	87	80
2.50	104	98	93	102	96	92	98	94	90	83
3.00	106	101	97	104	99	96	101	97	93	86
4.00	109	105	101	107	103	100	103	100	97	89
5.00	111	107	104	109	106	103	105	102	100	91
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2023-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 65.0%
 Test Distance: 7.560m [K=0.9974]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:221.5V I:0.1136A P:23.92W PF:0.9505 Lamp Flux:2961.5x1 lm		
NAME: 线条灯	TYPE:LED	WEIGHT:
SPEC.:LI-JE1200LM/W-CCT-SL-下发光-小蜂窝	DIM.: 60*75*1200	SERIAL No.:
MFR.: JT	SUR.:0.6*0.75*0.12	Shielding Angle:

Conical surface Flux(90deg):

2139.6 lm

%lum = 72.2%


%lamp = 72.2%

Conical surface Flux(120deg):

2655 lm

%lum = 89.6%

%lamp = 89.6%




C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2023-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.560m [K=0.9974]
Remarks:

AAI Figure

Test:U:221.5V I:0.1136A P:23.92W PF:0.9505 Lamp Flux:2961.5x1 lm		
NAME: 线条灯	TYPE:LED	WEIGHT:
SPEC.:LI-JE1200LM/W-CCT-SL-下发光-小蜂窝	DIM.: 60*75*1200	SERIAL No.:
MFR.: JT	SUR.:0.6*0.75*0.12	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2023-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.560m [K=0.9974]
Remarks:

ISOLUX DIAGRAM

Test:U:221.5V I:0.1136A P:23.92W PF:0.9505 Lamp Flux:2961.5x1 lm		
NAME: 线条灯	TYPE:LED	WEIGHT:
SPEC.:LI-JE1200LM/W-CCT-SL-下发光-小蜂窝	DIM.: 60*75*1200	SERIAL No.:
MFR.: JT	SUR.:0.6*0.75*0.12	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2023-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.560m [K=0.9974]
Remarks:

LED Avg.L Report

Test:U:221.5V I:0.1136A P:23.92W PF:0.9505 Lamp Flux:2961.5x1 lm		
NAME: 线条灯	TYPE:LED	WEIGHT:
SPEC.:LI-JE1200LM/W-CCT-SL-下发光-小蜂窝	DIM.: 60*75*1200	SERIAL No.:
MFR.: JT	SUR.:0.6*0.75*0.12	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	7254
L_0~180 (75) av	6402
L_0~180 (85) av	4773
L_90~270 (65) av	8195
L_90~270 (75) av	7054
L_90~270 (85) av	6153
L_45 (65) av	7842
L_45 (75) av	6809
L_45 (85) av	5635

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2023-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.560m [K=0.9974]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2023-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 7.560m [K=0.9974]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:7.560m [K=0.9974]
Remarks:

```